



Add: Building G, Runhe Industrial Zone, Zhentou Industrial Avenue, Xinqiao Street,
BaoAn ShenZhen, Guangdong Province, China.

Tel: 0755-23200658, 23200758, 23200858

Fax: 0755-23200958

Web: <http://www.flourishe.com>

E-mail: sales@flourishe.com

FL-617 Type Automatic Tube-sleeving Machine For Tubular Fuses (vertical)



	电子元件	A:6.5~25 B:105(Max) C: φ 0.6~ φ 1.0 D: φ 6.5(Max)	1、此表中所提供尺寸仅为常规机适应范围,超出此范围可接受订做;
	热缩管	$E=D+(1.2\sim 2.0)$	2、做前请提供组件、套管、成型形状尺寸等资料;
	铁氟龙管	$F=C+(0.5\sim 0.8)$	3、可通过更换模具成型成不同的形状;
	成型后	G=2.5(Min.) H=2.5(Min.) P: 固定, 依要求设计	4、可根据需要在同一台机上轻松实现如左图等成型形状的切换。

Spec

Input Power: 110V/220V AC 60HZ/50HZ

Size: L1300*W700*H1400MM

Weight: 350KG

Speed: 2500-3500PCS/H

Power: 1000W

Air pressure: 4-6kg/cm²



Features

- The machine is specially designed for sleeving, pins cutting and forming of bulk or belted tubular fuses, and can sleeve heat shrinkable tube on tubular fuses or Teflon tube on both pins or sleeve both types of tubes together.
- A special vibrating disk is equipped to feed bulk tubular fuses automatically.
- Automation process: cut belts (or feed bulk tubular fuses)- clamp tubular fuses - line up pins - sleeve tubes on fuses- tubes shrink- sleeve Teflon tubes on pins - form - cut pins - discharge.

24-hour customer service hotline 18038071048

18902437001



深圳市富诺威电子科技有限公司
SHEN ZHEN FLOURISH ELECTRONICS TECHNOLOGY CO.,LTD.

Add: Building G, Runhe Industrial Zone, Zhentou Industrial Avenue, Xinqiao Street,
BaoAn ShenZhen, Guangdong Province, China.

Tel: 0755-23200658, 23200758, 23200858

Fax: 0755-23200958

Web: [Http://www.flourishe.com](http://www.flourishe.com)

E-mail: sales@flourishe.com

-
- Belted components are fed by special gears automatically, and bulk components by a vibrating disk.
 - Replaceable forming dies are easy to install, remove and replace.
 - The mechanical transmission structure and durable imported cams (guaranteed for 10 years) are used to guarantee that the machine works with high stability and precision.
 - The machine is featured by its frame made from Aluminum profile, compact structure and smaller dimension, and processing rate: 1500 pcs/hour at best.
 - It is equipped with Panasonic PLC and touch screen for precise control.
 - It is also equipped with durable imported SMC or Air TAC cylinder, magnet switch and solenoid valve.
 - The machine is widely used by factories producing power supplies based on its high stability and automation and can substitute for 3 - 8 workers.