



深圳市富诺威电子科技有限公司
SHEN ZHEN FLOURISH ELECTRONICS TECHNOLOGY CO.,LTD.

Add: Building G, Runhe Industrial Zone, Zhentou Industrial Avenue, Xinqiao Street,
BaoAn ShenZhen, Guangdong Province, China.

Tel: 0755-23200658, 23200758, 23200858

Fax: 0755-23200958

Web: [Http://www.flourishe.com](http://www.flourishe.com)

E-mail: sales@flourishe.com

FL-915A Type Full Automatic Triode -radiators Screwing Machine



Spec

Input Power: 220V AC. 50HZ

Size: L1700×W1500 ×H1600mm

Air pressure: 4-6Kg

Triode package: Tube or loose

Radiator package: Loose

Efficiency: 1000-1200PCS/H

Power: 1500W

Weight: 650kg

Introduction

- The equipment is designed specially to screw triodes(MOS tubes)on radiators automatically.
- The equipment adopts the working principle of turntable high-precision separator al actions are divided in order, the divided into the following two types:

(1)Transistor nut radiator locking: The rut automatically is fed by vibrating plate-Manipulator grabs the fixture of automatic feeding on the turntable--Tube or loose triodes automatically forming and

24-hour customer service hotline 18038071048 18902437001



深圳市富诺威电子科技有限公司
SHEN ZHEN FLOURISH ELECTRONICS TECHNOLOGY CO.,LTD.

Add: Building G, Runhe Industrial Zone, Zhentou Industrial Avenue, Xinqiao Street, BaoAn
ShenZhen, Guangdong Province, China.

Tel: 0755-23200658, 23200758, 23200858

Fax: 0755-23200958

Web: [Http://www.flourishe.com](http://www.flourishe.com)

E-mail: sales@flourishe.com

shears arrangement---Automatic feeding on the nut in the fixture---Apply radiator oil---Place the radiator on the triode---The screw automatically feeds and locks---After locking the product, take out the product by manipulator. And so on and so on.

(2)Transistor nut-free radiator locking: Radiator is placed on fixture--Tube triode(MOS)is lined up and fed automatically--After cutting forming and apply radiator oil, processed triodes are clamped and positioned on radiator for locking automatically, one radiator can be locked with several triodes(MOS) at different station----After locking the product, take out the product by manipulator. And so on and so on.

- All locking actions are completed automatically. Different dies can be installed to process different radiators, and one radiator is screwed with 3triodes (MOS) at most in general, but more stations can be customized for locking more screws on one radiator.
- All locking actions are completed automatically. Different dies can be installed to process different radiators, and one radiator is screwed with 3triodes (MOS) at most in general, but more stations can be customized for locking more screws on one radiator.
- The machine is equipped with Mitsubishi PLC and touch screen for precise control.
- Separators position component precisely to keep high stability and get a higher qualified rate.
- It can substitute for several workers based on its high automation, and so it is widely used by factories producing power supplies.